

Hy-Lok®

Heat Exchanger Tube Plugs



■ Features :

- Extends the Life of Heat Exchanger Tube Bundles
- Easy Installation
- Positive Sealing
- Low Cost

■ Tube Wall Gage and Thickness Standards

| Wall Gage | Wall Thickness in. (mm) |
|-----------|--------------------------------|
| 11 to 14 | 0.083 to 0.120 (2.1 to 3.0) |
| 12 to 17 | 0.058 to 0.109 (1.5 to 2.8) |
| 15 to 20 | 0.035 to 0.072 (0.9 to 1.8) |

Note : Wall gage and thickness based on Birmingham (Stub's Iron) Wire Gage System.

Dimensions

| | Part Number | T Tube O.D. in.(mm) | † Tube Wall Gage | D | d | L |
|--|---------------|---------------------------|------------------------|-----------------|-----------------|----------------|
| | | | | in. (mm) | | |
| | CHETP 8-11-14 | 1/2 (12.7) | 11 to 14 | 0.366 (9.3) | 0.280 (7.1) | 1.55 (39.4) |
| | CHETP 8-15-20 | | 15 to 20 | 0.457 (11.6) | 0.371 (9.4) | 1.56 (39.6) |
| | CHETP10-11-14 | 5/8 (15.9) | 11 to 14 | 0.491 (12.5) | 0.405 (10.3) | 1.57 (39.9) |
| | CHETP10-15-20 | | 15 to 20 | 0.582 (14.8) | 0.496 (12.6) | 1.58 (40.1) |
| | CHETP12-11-14 | 3/4 (19.1) | 11 to 14 | 0.616 (15.6) | 0.530 (13.5) | 1.58 (40.1) |
| | CHETP12-12-17 | | 12 to 17 | 0.663 (16.8) | 0.546 (13.9) | 2.09 (53.1) |
| | CHETP12-15-20 | | 15 to 20 | 0.707 (18.0) | 0.621 (15.8) | 1.59 (40.4) |
| | CHETP14-11-14 | 7/8 (22.2) | 11 to 14 | 0.741 (18.7) | 0.650 (16.5) | 1.60 (40.6) |
| | CHETP14-15-20 | | 15 to 20 | 0.832 (21.1) | 0.746 (18.9) | 1.62 (41.1) |
| | CHETP16-11-14 | 1 (25.4) | 11 to 14 | 0.866 (22.0) | 0.780 (19.8) | 1.62 (41.1) |
| | CHETP16-12-17 | | 12 to 17 | 0.908 (23.1) | 0.794 (20.1) | 2.11 (53.6) |
| | CHETP16-15-20 | | 15 to 20 | 0.957 (24.3) | 0.871 (22.1) | 1.63 (41.4) |

■ How To Order

Use BRAS for brass, S316 for 316 stainless steel, MONE for Alloy R405, or STEL for carbon steel as a prefix to the Part Number ; Example : CHETP 8-15-20-S316



HY-LOK CORPORATION

© 2001 HY-LOK CORPORATION all rights reserved