

# 2S Direct Drive Solenoid Valve



## Ordering Code

<b>2W</b>	<b>150</b>	—	<b>15</b>	<b>AC220V</b>
Series Code 2S: Stainless Steel 304 or 316	Aperture: 120:12mm 150:15mm 200:20mm 250:25mm 320:32mm 400:40mm 500:50mm		Port Size: 10: G3/8" 15: G1/2" 20: G3/4" 25: G1" 35: G1 1/4" 40: G 1 1/2" 50: G2"	Voltage: AC380V AC220V AC110V AC36V AC24V DC12V DC24V



## Specification

Model	2S120-10	2S150-15	2S200-20	2S250-25	2S320-35	2S400-40	2S500-50
Body Material	Stainless Steel 304 or 316						
Control Method	Direct lifting diaphragm construction						
Pipe Size	G3/8"	G1/2"	G3/4"	G1"	G1 1/4"	G1 1/2"	G2"
Nominal Diameter (mm)	12	15	20	25	32	40	50
Applicable Medium	Air, Gas, Water, Oil, Petroleum, etc.						
Type	Normal closed or Normal open						
Pressure Range	0~0.8 M Pa						
Medium Temperature	NBR Seal -5°C ~80°C/EPDM Seal:-5°C ~120°C/VITON seal: -5°C ~150°C						
Specified Voltage	AC220V, DC24V, AC110V, DC12V, AC24V,etc.						
Operating Voltage Range	± 10%						
Min. Activating Time	0.05S						
Install Method	Horizontal Installation						

